

# Multi-Sile II

*THE LEADER OF THE PACK!*



## SMALL SQUARE BALER, LARGE ROUND & LARGE SQUARE BALER APPLICATOR GUIDE

**\*\* TANKS ARE AVAILABLE IN 25 OR 50 GALLON SIZE \*\***

- 1) Find a center location on top of pick up for mounting the frame. Place a 2x4 under the frame at the top of the baler. Drill holes, insert bolts and secure tightly.



- 2) Face the tank numbers towards the tractor and mount the tank, secure with ratchet straps; that are cut to length.



- 3) Thread the pressure gauge with nylon tape and install on tank fitting.
- 4) Bring hose off of the pump to the top of the opening, making sure to install the filter between the pump and the -T- fitting. Use hose clamps to tighten.
- 5) Place 2 nozzles so they spray into the pickup. Put yellow tips in nozzles.



- 6) Run Hose from the -T- to the tips. Secure with hose clamps.
- 7) Zip tie brackets to tips to keep the nut from loosening.
- 8) Run wire from pump to the hitch, **Make sure it is out of the way of all moving parts.**
- 9) Install the 2 prong connection for quick hitch.

10) Find optimum place to mount controller in operator station or cab of tractor.



11) Run red wire to power, the black wire is a ground wire.

12) Install green & white plug, run wire to 2 prong quick connect from baler.

13) Turn controller on, red light should come on, if it doesn't you don't have power to the red wire.

Deaton Nutrition  
N4852 Cty Rd. C  
Ellsworth, WI 54011  
Office: 715-273-3739  
Cell: 612-812-7939  
[deatonnutrition@dishup.us](mailto:deatonnutrition@dishup.us)